

**TYPICAL
DRIVEWAY CULVERT**

- * RESIDENTIAL DRIVEWAY
- ** COMMERCIAL DRIVEWAY (26,000 LBS OR LESS TRUCKS)
- *** COMMERCIAL DRIVEWAY (26,001 LBS OR MORE TRUCKS)

NOTE:

1. LENGTHEN CULVERTS AS REQUIRED TO ACCOMMODATE DEEPER ROADSIDE DITCHES. CULVERTS MUST BE LONGER THAN MINIMUM LENGTH LISTED.
2. STANDARD CULVERT SIZE TO BE 12" DIAMETER. LARGER DIAMETER PIPE MAY BE REQUIRED FOR HIGHER FLOW.
3. USE 16 GAUGE CMP OR CLASS 3 CONCRETE PIPE FOR 12"-24" PIPE DIAMETERS. USE OF N-12 PLASTIC PIPE ALLOWED FOR 12"-24" PIPE DIAMETERS WITH ENGINEER OF RECORD APPROVAL, AND ADEQUATE COVER PER PIPE MANUFACTURER. PIPE DIAMETERS OVER 24" MUST BE REVIEWED AND APPROVED BY COUNTY ENGINEER.

JACKSON COUNTY ROADS


MIKE KUNTZ, P.E.
COUNTY ENGINEER

Date	By	Revision

**JCRD701:
DRIVEWAY CULVERT**

\\Engineering\LIBRARY\COUNTY\STD_DWG\CURRENT\RD700-CurbSidewalkDriveway\JCRD701-DrivewayCulvert.dwg

OCT 2017 NO SCALE



**JACKSON
COUNTY**
Roads